

## 26 507 AL0 EUPHORIA SMARTCONTROL SYSTEM 310 DUO SHOWER SYSTEM WITH THERMOSTAT FOR WALL MOUNTING



### PRODUCT DESCRIPTION

- Tyc: brushed hard graphite
- consisting of:
  - horizontal 450 mm shower arm
  - upper bracket adjustable for minimal adaption to existing drilling holes
  - exposed SmartControl thermostat
- allows change between:
  - head shower Rainshower SmartActive 310
- 2 spray patterns:
  - maximum flow rate (at 3 bar): 20 l/min
  - GROHE PureRain, ActiveRain
- hand shower Euphoria 110 Massage, spray plate white
- 3 spray patterns:
  - Rain, SmartRain, Massage
  - maximum flow rate (at 3 bar): 16 l/min
  - adjustable in height with gliding element
- Silverflex shower hose 1750 mm 1/2" x 1/2" (28 388)
- GROHE DreamSpray perfect spray pattern
- GROHE Long-Life finish
- GROHE CoolTouch no risk of scalding
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE ProGrip with knurl structure
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C included
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- integrated GROHE EasyReach shower tray
- SpeedClean anti-limescale system
- Inner WaterGuide for a longer life
- TwistStop to prevent hose from twisting
- suitable for instantaneous heaters from 18 kW/h
- minimum flow rate 5 l/min