


## 26 507 DC0 EUPHORIA SMARTCONTROL SYSTEM 310 SHOWER SYSTEM WITH THERMOSTAT FOR WALL MOUNTING



### PRODUCT DESCRIPTION

- Tyc: supersteel
- consisting of:
  - horizontal 450 mm shower arm
  - upper bracket adjustable for minimal adaption to existing drilling holes
  - exposed SmartControl thermostat
- allows change between:
  - head shower Rainshower SmartActive 310
  - spray patterns: GROHE PureRain, ActiveRain
  - maximum flow rate (at 3 bar): 20 l/min
  - hand shower Euphoria 110 Massage, spray plate white
  - spray patterns: Rain, SmartRain, Massage
  - maximum flow rate (at 3 bar): 16 l/min
  - adjustable in height with gliding element
  - shower hose Silverflex 1750 mm 1/2" x 1/2" (28 388)
- GROHE DreamSpray - perfect spray pattern
- GROHE LongLife finish
- GROHE CoolTouch - no risk of scalding
- GROHE TurboStat - compact cartridge with wax thermoelement
- GROHE ProGrip - with knurled structure
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus - optional temperature limiter at 43°C included
- GROHE SmartControl - control the shower with intuitive push/turn button
- integrated GROHE EasyReach shower tray
- GROHE SpeedClean - effortless limescale removal
- Inner WaterGuide - inner insulation for surface protection
- TwistStop - to prevent hose from twisting
- suitable for instantaneous heaters from 18 kW/h
- minimum flow rate 5 l/min