



## 26 657 000 RAINSHOWER SMARTACTIVE 310 SHOWER SYSTEM WITH BATH THERMOSTAT FOR WALL MOUNTING



### PRODUCT DESCRIPTION

- Tyc: Chrome
- consisting of:
  - horizontal swivable 450 mm shower arm
  - exposed thermostat with Aquadimmer function
  - allows change between:
    - head shower Rainshower Mono 310
    - maximum flow rate (at 3 bar): 7.5 l/min
  - with ball joint
  - rotation angle  $\pm 15^\circ$
- bath inlet
- separate diverter for hand shower
- hand shower Rainshower SmartActive 130
- maximum flow rate (at 3 bar): 8.5 l/min
- adjustable in height with gliding element
- including performance grip
- Silverflex shower hose 1750 mm
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE Water Saving - Less water, perfect flow
- GROHE SafeStop safety button at 38°C ( calibration required )
- GROHE SafeStop Plus optional temperature limiter at 43°C included
- GROHE CoolTouch no risk of scalding
- GROHE DreamSpray perfect spray pattern
- GROHE SmartTip showering spray selection via push of a ring
- GROHE Long-Life finish
- GROHE FastFixation (upper bracket adjustable for adaption to existing drilling holes)
- SpeedClean anti-limescale system
- Inner WaterGuide for a longer life
- suitable for instantaneous heaters from 18 kW/h
- minimum flow rate 5 l/min