

26 836 AL0 RAINSHOWER SMARTACTIVE 310 SHOWER SYSTEM WITH THERMOSTAT FOR WALL MOUNTING



PRODUCT DESCRIPTION

- Tyc: brushed hard graphite
- consisting of:
 - horizontal swivable 450 mm shower arm
 - exposed thermostat with Aquadimmer function
 - allows change between:
 - head shower Rainshower Mono 310
 - maximum flow rate (at 3 bar): 9.5 l/min
 - with ball joint
 - rotation angle $\pm 15^\circ$
 - hand shower Rainshower SmartActive 130
 - maximum flow rate (at 3 bar): 8.5 l/min
 - adjustable in height with gliding element
 - including performance grip
 - Silverflex shower hose 1750 mm
 - GROHE EcoJoy - Less water, perfect flow
 - GROHE TurboStat - compact cartridge with wax thermoelement
 - GROHE SafeStop safety button at 38°C (calibration required)
 - GROHE SafeStop Plus - optional temperature limiter at 43°C included
 - GROHE CoolTouch - no risk of scalding
 - GROHE DreamSpray - perfect spray pattern
 - GROHE SmartTip showering spray selection via push of a ring
 - GROHE LongLife finish
- Flexible Installation - 1 adjustable bracket for existing drill holes
- GROHE SpeedClean - effortless limescale removal
- suitable for instantaneous heaters from 18 kW/h
- minimum flow rate 5 l/min
- DR-brass



